



DOSAL


WORKING CONDITIONS

Max working pressure _____ 7 bar (101 psi)
 Max working temperature _____ 35°C (95°F)
 Min working temperature _____ 4°C (39,2°F)
 Max total hardness _____ 50°F (500 ppm CaCO₃)

Remark - Water treated with polyphosphate can be heated up to a max temperature of 75° - 80°C, beyond that temperature the polyphosphate gradually loses its efficacy.

SPECIFICATIONS

Non-toxic materials, suitable for drinking water.
 Head: reinforced polypropylene.
 Bowl: SAN.
 O-ring: EPDM.
 Flat seals: PVC.
 Treating material: sodium polyphosphate crystals.



DOSAL is a non-proportional dosing systems designed for the protection of washing-machines against the calcareous incrustations of the heater, saving energy, reducing powders consumption and providing "spotless" aesthetic effect on items.
 DOSAL is designed for easy installation to standard water supply of washing machines, no plumbing required.



DOSAL for washing machine

POLYPHOSPHATE CRYSTALS DOSING SYSTEMS

| CODE | MODEL | APPLICABLE REFILL | IN/OUT | THREADS | DIMENSIONS mm | | |
|-----------|-------|--------------------|--------|-------------|---------------|----|----|
| | | | | | A | B | C |
| RA402P442 | DOSAL | LOOSE CRYSTAL 6/10 | 3/4" | PLASTIC-BSP | 130 | 68 | 68 |



POLYPHOSPHATE CRYSTALS 6/10 (small)
 160 g blister, refill TO DOSAL.

