




MAG



WORKING CONDITIONS

Max working pressure _____ 10 bar (145 psi)
 Max working temperature _____ 90°C (194°F)
 Min working temperature _____ 4°C (39,2°F)
 Max total hardness _____ 35°F (350 ppm CaCO₃)

Remark - Water treated can be heated up to a max temperature of 90°C, beyond that temperature the conditioning gradually loses its efficacy.

SPECIFICATIONS

Non-toxic materials, suitable for drinking water.
 Body MAG MF and MAG MM: CW 614 N brass chromium-plated.
 Body MAG FF: aluminium.
 Magnets: neodymium.
 Magnetic induction: 12.800 GAUSS.

Magnetic conditioning of hard water provides anti-scale protection by making the carbonates unable to deposit and form incrustation on water heaters and pipes, thus reducing energy consumption and prolonging the lifetime of appliances. MAG is a range of magnetic conditioners made of chrome-plated brass and neodymium magnets with magnetic induction up to 12800 gauss, in compliance with UE directive 98/83/CE.

MAG MF magnetic anti-scale conditioners

WITH IN/OUT THREADS MALE/FEMALE

| CODE | MODEL | IN/OUT | THREADS | DIMENSIONS mm | | |
|-----------|----------------------------------|--------|-----------------|---------------|----|----|
| | | | | A | B | C |
| RE6115000 | Micro MAG MF | 1/8" | MALE-FEMALE BSP | 56 | 30 | 30 |
| RE6115001 | MAG 1 MF complete with two seals | 1/2" | MALE-FEMALE BSP | 73 | 35 | 35 |
| RE6115002 | MAG 2 MF complete with two seals | 3/4" | MALE-FEMALE BSP | 88 | 35 | 35 |



MAG MM magnetic anti-scale conditioners

WITH IN/OUT THREADS MALE/MALE

| CODE | MODEL | IN/OUT | THREADS | DIMENSIONS mm | | |
|-----------|-----------|--------|---------------|---------------|----|----|
| | | | | A | B | C |
| RE6115003 | MAG 3 MM | 1" | MALE-MALE BSP | 89 | 50 | 50 |
| RE6115011 | MAG 11 MM | 1"1/4 | MALE-MALE BSP | 135 | 80 | 80 |
| RE6115012 | MAG 12 MM | 1"1/2 | MALE-MALE BSP | 135 | 80 | 80 |
| RE6115013 | MAG 13 MM | 2" | MALE-MALE BSP | 135 | 80 | 80 |



MAG FF magnetic anti-scale conditioners

WITH IN/OUT THREADS FEMALE/FEMALE

| CODE | MODEL | IN/OUT | THREADS | DIMENSIONS mm | | |
|-----------|-----------|--------|-------------------|---------------|----|----|
| | | | | A | B | C |
| RE6115103 | MAG 3 FF | 1" | FEMALE-FEMALE BSP | 135 | 80 | 80 |
| RE6115111 | MAG 11 FF | 1"1/4 | FEMALE-FEMALE BSP | 135 | 80 | 80 |
| RE6115112 | MAG 12 FF | 1"1/2 | FEMALE-FEMALE BSP | 135 | 80 | 80 |
| RE6115113 | MAG 13 FF | 2" | FEMALE-FEMALE BSP | 135 | 80 | 80 |

